



BOTTLE FILLING MACHINE AUTOMATIC

SPECIFICATIONS

CAPACITY	:	4-6 BOTTLES/MINUTE (APPROX)
MOTOR	:	0.25 HP
DIMENSIONS	:	1'X1.5'X1' (LXBXH)
BODY	:	STAINLESS STEEL 304 GRADE



DECOTICATOR WITH GRADER FOR GROUNDNUT

SPECIFICATIONS

**2 HP-3 & 1 PHASE
MS BODY
WITH BLOWER FAN
400 KG GROUNDNUT PER HOUR
WITH GRADER**

**USE FOR
DECOTICATING
GROUNDNUT**



MINI ROATARY 30 KG/HR

SPECIFICATIONS

CAPACITY	:	30 KG./HR
MOTOR	:	5HP PH
POWER CONSUMPTION	:	3 UNIT/HR.
DIMENSIONS	:	4'X2'X4' (LXBXH)
HOPPER & OIL TRAY	:	STAINLESS STEEL 304 GRADE
URAL	:	FG 30 GRADE CASTING
ULAKAI	:	FG 30 GRADE CASTING
AXIL SHAFT	:	EN 19 GRADE SHAFT



AUTOMATIC OIL FILTER PRESS

SPECIFICATIONS

CAPACITY	:	100 LTR/HR.
MOTOR & PUMP	:	1HP-3P/1PH
POWER CONSUMPTION	:	0.75 UNIT / HR.
DIMENSIONS	:	5' X 2'X4' (LXBXH)
BODY	:	MILD STEEL WITH SS 304 OIL TRAY
FILTER PLATES	:	POLYPROPYLENE (18" X 18")
CLOTH	:	COTTON/PP/NON WOVEN/SPUN



COMMERCIAL OIL EXTRACTION MACHINE

SPECIFICATIONS

MOTOR CAPACITY	:	2 HP/3 HP.(SINGLE PHASE)
CRUSHING CAPACITY	:	20 TO 30 KG/HR (APPROX)
POWER CONSUMPTION	:	1 TO 1.5 UNIT / HR. (APPROX)



ROTARY-60KG/HR

SPECIFICATIONS

CAPACITY	:	60KG./HR
POWER REQUIRED	:	10 HP/7.5 HP -3 PHASE
MOTOR TYPE	:	960 RPM "A" CLASS WINDINGS
POWER CONSUMPTION	:	5 TO 7.5 UNITS/HR. (APPROX)
MAIN SHAFT	:	EN 8 GRADE 4 INCH DIA HARDENED MATERIAL
MACHINE SIZE	:	6 X 2 X 6 FT (LBH)
BRANDED BEARINGS		
IMPORTED BELT		
TVS BOLT NUTS		
MACHINE RPM 36		
URAL CASTING IS OF FG 30 GRADE		
HEAVY BODY STRUCTURE		
STAINLESS STEEL 304 GRADE HOPPER AND OIL TRAY USED		
GEAR BOX CROWN PINION TYPE - HEAVY DUTY TYPE - FILLED WITH LONG LIFE GREASE		